

**In the Claims:**

Please cancel claims 4 and 5 without prejudice. The claims have been amended as follows:

1. **(Currently Amended)** An apparatus for monitoring the dynamic loading rate on support systems of a mobile roof support unit used in an underground mine to withstand abutment pressure, comprising:

at least one load sensing device adapted to be coupled to one or more of the support systems of the mobile roof support unit used in the underground mine;

a programmable controller for processing support system loading information received from said at least one load sensing device; and

a plurality of sensory indicators located in the vicinity of said at least one load sensing device and controlled by said programmable controller to provide timely warning indications used as an aid in determining when to install additional support systems and alert miners of dangerous loading conditions on the support systems of the mobile roof support unit during mining operations on a real-time basis.

2. **(Original)** An apparatus as recited in claim 1 wherein said load sensing device comprises a pressure transducer.

3. **(Original)** An apparatus as recited in claim 1 wherein said load sensing device comprises a strain gauge.

4. **(Canceled)**

5. **(Canceled)**

6. **(Currently Amended)** An apparatus as recited in claim 1 wherein said programmable controller comprises an embedded microprocessor ~~having based system~~.

7. (Original) An apparatus as recited in claim 1 wherein said programmable controller monitors loading rate changes on said load sensing device installed on the support systems.

8. (Original) An apparatus as recited in claim 7 wherein said programmable controller calculates the loading rates on said load sensing device.

9. (Original) An apparatus as recited in claim 7 wherein said plurality of sensory indicators comprise various color visual indicators including multicolor strobes, light-emitting diodes (LEDs), fluorescent visual indicators and the like.

10. (Original) An apparatus as recited in claim 9 wherein said programmable controller is programmed to sequentially activate different color lights as the loading rate increases on the support systems.

11. (Original) An apparatus as recited in claim 7 wherein said plurality of sensory indicators comprise audible alarm indicators.

12. (Currently Amended) An apparatus for monitoring the dynamic loading rate on support systems of a mobile roof support unit used in an underground mine to withstand abutment pressure, comprising:

~~means for installing~~ at least one load sensing device ~~on one or more of the support systems used in the underground mines~~ coupled to one or more of the support systems of the mobile roof support unit;

means for receiving support system loading information from said at least one load sensing device;

means for determining the loading rate on the support systems using the received loading information; and

means for activating sensory warning indicators located in the vicinity of said at least one load sensing device responsive to said determining means to provide timely warning indications used as an aid in determining when to install additional support systems and alert miners of

dangerous loading conditions on the support systems of the mobile roof support unit during mining operations on a real-time basis.

13. (Original) An apparatus as recited in claim 12 wherein said determining means identifies changes in the loading rate on the support systems.

14. (Currently Amended) An apparatus as recited in claim 13 further comprising means for sequentially activating different color lights and audio alarms as the loading rate increases on the support systems.

15. (Currently Amended) A method of monitoring the dynamic loading rate on support systems of a mobile roof support unit used in an underground mine to withstand abutment pressure, the method comprising:

~~installing at least one load sensing device on one or more of the support systems used in the underground mines;~~

receiving support system loading information from ~~the~~ at least one load sensing device coupled to the support systems of the mobile roof support unit;

determining the load rate on the support systems using the received loading information; and

activating sensory warning indicators located in the vicinity of said at least one load sensing device to provide timely warning indications used as an aid in determining when to install additional support systems and alert miners of dangerous loading conditions on the support systems of the mobile roof support unit during mining operations on a real-time basis.

16. (Currently Amended) A method as recited in claim 15 ~~comprising the step of~~ wherein determining the load rate on the support systems comprises identifying changes in the loading rate on the support systems.

17. (Original) A method as recited in claim 16 wherein said activating step provides warning indications in response to said identifying step.

18. (Original) A method as recited in claim 17 comprising the step of sequentially activating different color lights as the loading rate increases on the support systems.

19. (Currently Amended) The method as recited in claim 15 **further comprising:**  
**wherein hydraulically coupling at least one of the load sensing devices device is hydraulically coupled to one or more of the support systems in the installing step of the mobile roof support unit during installation.**

20. (Currently Amended) A method as recited in claim 15 **further comprising:**  
**wherein welding at least one of the load sensing devices device is welded onto the support systems in the installing step during installation.**

21. (Currently Amended) An apparatus for monitoring the dynamic loading rate on support systems **of a mobile roof support machine** to withstand abutment pressure, comprising:

at least one load sensing device adapted to be coupled to one or more of the support systems **of the mobile roof support machine;**

a programmable controller for processing support system loading information received from said at least one load sensing device; and

at least one sensory indicator located in the vicinity of said at least one load sensing device and controlled by said programmable controller to provide timely warning indications used as an aid in determining when to install additional support systems and alert workers of dangerous loading conditions on the support systems **of the mobile roof support machine** on a real-time basis.

22. (Previously Presented) The apparatus of claim 12 wherein the means for determining support system loading information is programmable.

23. (Previously Presented) The method of claim 15 wherein the determining is performed by a programmable controller.

24. (Currently Amended) An apparatus for monitoring the dynamic loading rate on support systems of a mobile roof support unit to withstand abutment pressure, comprising:

at least one load sensing device adapted to be coupled to one or more of the support systems of the mobile roof support unit to monitor pressure inside one or more hydraulic jacks associated with the mobile roof support unit;

a programmable controller for processing support system loading information received from said at least one load sensing device; and

at least one sensory indicator located in the vicinity of said at least one load sensing device and controlled by said programmable controller to alert workers of dangerous loading conditions on the support systems of the mobile roof support unit on a real-time basis.

25. (New) The apparatus as recited in claim 1 comprising at least one sensory indicator indicating safe conditions in the underground mine.

26. (New) The apparatus of claim 25 wherein the at least one sensory indicator indicating safe conditions in the underground mine comprises a green light.

27. (New) The apparatus as recited in claim 12 wherein the means to provide timely warning indications used as an aid in determining when to install additional support systems and alert miners of dangerous loading conditions on the support systems during mining operations comprises an indicator indicating safe conditions.

28. (New) The apparatus as recited in claim 27 wherein the indicator indicating safe conditions comprises a green light.

29. (New) One or more computer-readable media comprising computer-executable instructions for performing the method of claim 15.

30. (New) The apparatus of claim 1 wherein the programmable controller comprises a communications interface operable to receive values for controlling the sensory indicators.

31. (New) The apparatus of claim 12 wherein the means for activating sensory warning indicators is operable to receive a value via a communications interface means, and the value affects under what conditions the sensory warning indicators are activated.

32. (New) The method of claim 15 further comprising setting a value received via a communications interface, wherein the value affects activation of one or more sensory warning indicators.

33. (New) The apparatus of claim 21 wherein the programmable controller is operable to set one or more programmable values which help determine when to install additional support systems and alert workers of dangerous loading conditions on the support systems.

34. (New) The apparatus of claim 24 wherein the programmable controller is operable to set programmable values based at least in part on the loading conditions on the support systems.

35. (New) The apparatus of claim 1 wherein the mobile roof support unit comprises a mobile retreat mining unit with a plurality of hydraulic cylinder support systems, crawler tracks, and a canopy, said mining unit used to withstand the abutment pressure of the underground mine.

36. (New) The apparatus of claim 1 wherein the at least one load sensing device adapted to be coupled to one or more of the support systems of the mobile roof support unit used in the underground mine monitors pressure inside one or more hydraulic jacks associated with the mobile roof support unit.

37. (New) The apparatus of claim 12 wherein the means for determining the loading rate on the support systems using the received loading information comprises means to monitor pressure inside one or more hydraulic jacks.

38. (New) The apparatus of claim 21 wherein at least one load sensing device adapted to be coupled to one or more of the support systems of the mobile roof support machine comprises a pressure transducer to monitor pressure inside one or more hydraulic jacks associated with the mobile roof support machine.